

fastATE[®]
Technology



Off-Line Base
Test Platforms



6TL OFF-Line Base Test Platforms

6TL offers a variety of Off-Line Base Test Platforms in the form of modular 19-inch EIA rack cabinets, with unique design features that make them ideal to meet the needs of Automatic Test Equipment integrators. A selection of options and accessories will provide flexibility to meet the vast majority of racking applications in the field of ATE.

Standard Off-Line Base test platform includes:

- Solid base
- Leveling screws
- Heavy duty casters (Diameter 30mm)
- Uninterrupted Power Supply 1000VA (Customer should specify 110V or 220V when ordering)
- Man Machine Interface and Power Management unit (MMI)
- Virginia Panel Receiver (except 6TL 23 and 6TL 28)
- Ventilation
- Doors with lock
- Easy to remove side panels, which can be lifted off
- Combination of 6TL color and RAL 7035 gray



Feature List		6TL10	6TL19	6TL22	6TL23T
General	Power Requirements	220-230 V _{AC} 50-60 Hz	220-230 V _{AC} 50-60 Hz	220-230 V _{AC} 50-60 Hz	220-230 V _{AC} 50-60 Hz
	Weight	25 Kg	130 Kg	155 Kg	170 Kg
	Dimensions (WxDxH)	566 x 759 x 599 mm	566 x 800 x 813mm	566 x 824 x 1372 mm	566x1391x1372 mm
	Packaging	P/N 695108 67x86x70	P/N AA540 106x68x150; 40Kg	P/N AA540 106x68x150; 40Kg	P/N AF287 106x68x150; 40Kg
Mechanic infrastructure	Rack type	Benchtop sit-down	Half rack stand-up	Half rack + top stand-up	Full rack sit-down
	19" Free Rack space	7	11	7/11	8/15
	Rack depth	334 mm	530 mm	334mm / 530mm	530 mm
	Ventilation	2x Extractor Fans	2x Extractor Fans	2x Extractor Fans	2x Extractor Fans
	Cable Management	Cable ducts so that instrumentation wiring is properly organized. Easy Access			
	Casters	No	30mm, 2 lockable	30mm, 2 lockable	30mm, 2 lockable
Safety infrastructure	Emergency power off	Yes, H73000301	Yes, H73000301	Yes, H73000301	Yes, H73000301
	Circuit Protection	Yes, H73000301	Yes, H73000301	Yes, H73000301	Yes, H73000301
	Temperature monitoring	Yes, H73000301	Yes, H73000301	Yes, H73000301	Yes, H73000301
Power infrastructure	Power Distribution Units	Option	Option	Option	Option
	UPS	1000 VA	1000 VA	1000 VA	1000 VA
Fixture & Mass Interconnect	Receiver type / Capacity	S6 / 6 slots	S6 / 6 slots or G12 / 12 slots	G12 / 12 slots	G12 / 12 slots or G12/18 slots
	Fixture type	Manual Operated fixture	Manual Operated fixture	Manual Operated fixture	Manual Operated fixture
Options					
Power Management Unit (MMI)	Power Distribution Unit (PDU)	H730008xS	✓	✓	✓
	19" Power Management and MMI unit, Lite version	H73000301	✓	✓	✓
	CAN bus Power Management & MMI module, 19 inch 3U. Monophase 15A	H73000700	-	-	-
Beacon	CAN bus controller Three color light tower	H78001000	✓	✓	✓
Temperature, Pressure & Humidity Sensor	CAN Bus °C, %RH & hPa Transmitter	AK087	✓	✓	✓
Receiver VPC	6-Slots S6 VPC Receiver	310122100	✓	✓	-
	12-Slots G12 VPC Receiver	310104325	-	✓	✓
	18-Slots G12X VPC Receiver	310104386	-	-	-
Platform Lifter	Adjustable working high position	H71006600	-	✓	✓
	Working area lifter with flipper servopusher	H71006900	-	-	-
Monitor & Keyboard	Monitor and Keyboard with adjustable side support	H71002190	-	✓	✓
	Monitor and Keyboard in drawer kit	H71007300	-	✓	✓
Controller (IPC)	Industrial PC 19" 4U, i7, 16GB RAM , 500GB SSD	MMIPC08	-	✓	✓



6TL23	6TL28T	6TL28	6TL29
220-230 V _{AC} 50-60 Hz 160 Kg 566x800x1372 mm P/N AF287 106x68x150; 40Kg	220-230 V _{AC} 50-60 Hz 200 Kg 596x1200x2113 mm P/N 695092 151x96x236; 113Kg	220-230 V _{AC} 50-60 Hz 200 Kg 596x753x2113 mm P/N 695092 151x96x236; 113Kg	220-230 V _{AC} 50-60 Hz 350 Kg 596x1327x2046 mm P/N 695092 151x96x236; 113Kg
Full rack sit-down 12/15 530 mm 2x Extractor Fans	Full rack stad-up 38 560 mm 2x Extractor Fans	Full rack stad-up 43 560 mm 2x Extractor Fans	Semi-automated rack stand-up 29 560/1040 mm 2x Extractor Fans
30mm, 2 lockable Yes, H73000301 Yes, H73000301 Yes, H73000301	30mm, 2 lockable Yes, H73000700 Yes, H73000700 Yes, H73000700	30mm, 2 lockable Yes, H73000700 Yes, H73000700 Yes, H73000700	30mm, 2 lockable Yes, H73000700 Yes, H73000700 Yes, H73000700
Option 1000 VA	Option 1000 VA	Option 1000 VA	Option 1000 VA
G2/ G10/ iCon Cable Harness Fixture	G12X / 18 slots Manual Operated fixture	G2/ G10/ iCon Cable Harness Fixture	G12X / 18 slots 6TL Servo operated Fixture
✓	✓	✓	✓
✓	✓	✓	-
-	-	-	✓
✓	✓	✓	✓
✓	✓	✓	✓
-	-	-	-
✓	✓	✓	✓
-	✓	✓	✓
✓	-	-	-
-	-	-	✓
✓	✓	✓	-
✓	✓	✓	✓
✓	✓	✓	✓

Enhance Your Instrument Investment

6TL racks are specifically designed for 6TL's test hardware, meaning that the racks include the pre-wiring for YAV modules behind the receiver. But 6TL racks will also be ready to accommodate non-6TL equipment, making them suitable for the customer of a mixed instrument environment.

Three types of rack are offered to fulfill any test system needs: Benchtop rack, Off-line sit down, and Off-Line stand-up.

6TL's core business

6TL's core business is to help test engineering groups to create their standard test platform, so that it results in a real modular and scalable test system. We can do it because we use the FastATE technology: Our engineers will select, together with customer's team, the 6TL Base test platform that better fits the scheduled production needs. The combination of the Base test platform with the 6TL modules (YAV modules, 19" rack modules, ...), together with the needed third party instrumentation (rack & stack or PXI), will result in a top class standard and modular ATE, that 6TL will be able to replicate as many times as desired, always keeping each cable and bolt as it was specified.

The value of 6TL FastATE Off-Line Base Test Platforms

6TL Off-Line base test platforms have been designed and engineered to save time and money for ATE integrators:

- Fully assembled rack**
 Customers receive 6TL racks fully assembled and ready for equipment installation. Options ordered will be integrated from factory, so that the Off-Line platform will be shipped, and will be ready to be used by the integrator straight away.
- Cable management**
 6TL Off-Line base test platforms, feature cable ducts for the internal proper distribution of cables. Added space in the rear doors will help for cabling purposes, and will also enhance air flow.
- Manage Power Requirements thanks to MMI and PDUs**
 The Power of the Off-Line base test platform is composed of an UPS and the Man Machine Interface & Power Manager system from 6TL (MMI). Both pieces of equipment are supplied

by default with each 6TL Off-Line base test platform. Mains voltage option must be specified from order (110 V or 220 V). The master switch of the Base test platform is part of the MMI, and is conveniently located on the front of the rack, providing easy access to turn the power on and off to the Power Distribution Unit (PDU) outlets, that should be ordered separately.

- Ventilation**
 System-generated heat is removed by natural convection through a ventilation path incorporated in the top sides of the racks. For greater heat dissipation, a vented rear door (Option) can also help reducing the heat captured within the rack.
- Shelves**
 Sliding shelves and stationary shelves, to support instrumentation that does not have rack mount kits, are available for all 6TL base test platforms.
- Free EIA Units**
 Vertical space within test racks is measured in industry standard EIA units, where 1 EIA unit equals 44,5mm (1,75 inches). The number of free EIA units of the base test platform is necessary to understand whether all the instrumentation selected for the test application will fit inside the rack. 6TL offers a range of base test platforms with different free EIA rack units, from 7 EIA units in the benchtop 6TL10 to 43 EIA Units in the full rack 6TL28. All 6TL's base test platforms are delivered with filler panels to cover the free EIA units, and additional filler panels are available under request (1, 2, 3, 4 and 6 EIA Units).

- Package**
 Designed for easy unloading from the pallet.
- Packaging re-use**
 Packaging from 6TL is designed to be reused (either wood or hard corrugated paper).



Ordering Information

P/N	Description
H71001000	6TL-10 Bench Top Test Base Platform
H71001900	6TL-19 Off-Line Half Rack Base Test Platform
H71002200	6TL-22 Off-Line Test Platform
H71002300	6TL-23 Off-Line Rack type 15U Base Test Platform
H710023T00	6TL-23 Off-Line Rack type 15U Base Test Platform with receiver
H71002800	6TL-28 Off-Line Rack type 40U Base Test Platform
H710028T00	6TL-28 Off-Line Rack type 40U Base Test Platform with receiver
H71002900	6TL-29 Off-Line semi automatic Base Test Platform

Support:



Your project always on time, on budget and fulfilling the agreed specification

Close collaboration between 6TL and production team is important when starting to fit the FastATE concept into the customer process




Spare parts

Available spare part kits according to agreed 6TL warranty terms.



Repair Service

We are able to repair very fast any damaged part.



Product installation

6TL engineers may be available for installation of systems according to our guidelines and standards to secure the Start of Production date.



On-Site support

Whenever needed, 6TL technical staff is ready to help so that your line downtime is minimized.



Maintenance

Preventive maintenance plans